

<b>Product</b>	<b>Sinopec DOT 3 Synthetic Brake Fluid</b>
<b>Summary</b>	<p><b>Product description</b></p> <p>Sinopec DOT 3 Synthetic Brake Fluid is formulated using a blend of synthetic glycol ether with selected additives. It meets the requirements of the DOT 3 specification to give excellent brake and clutch performance, avoiding the problems of vapour lock and brake fade.</p>

Available sizes



1L



DRUM – 200L



IBC – 1000L



## Applications

Sinopec DOT 3 Synthetic Brake Fluid is suitable for use in:

- Hydraulic disc, drum and anti-skid brakes and clutch systems of all passenger cars and commercial vehicles that require a DOT 3 or DOT 3 performance synthetic fluid.

Caution: do not use where a mineral oil-based fluid or a DOT 5 silicone-based fluid is required.

## Features and benefits

- High performance of equilibrium reflux boiling point to resist the heat generated in high speed and overload vehicles while breaking.
- Excellent fluidity at low temperature.
- Works well with composite brake systems, in particular suitable for the rubber components, and protection the metal components.
- Excellent anti-rust, anti-corrosion, anti-oxidation and compatibility with rubber.

## Typical data

<b>Sinopec DOT 3 Synthetic Brake Fluid</b>	
Equilibrium reflux boiling point (ERBP), °C, ISO 4925	248
Wet ERBP, °C, ISO 4925	150
Kinematic viscosity, ISO 4925	
cSt @ -40°C	1170
cSt @ 100°C	2.115
pH, ISO 4925	9.0
Corrosion, 120 h @ 100°C, mass change of metal strips, mg/cm <sup>2</sup> , ISO 4925	
tinned iron	0.00
steel	0.00
aluminium	0.00
cast iron	0.00
brass	0.12
Copper	0.10
zinc	0.00
Effect on rubber, ISO 4925	Pass
styrene butadiene rubber (SBR) @ 120°C	
cup diameter increase, mm	0.75
hardness change, IRHD	6
ethylene propylene diene monomer (EPDM) @ 120°C	
volume change, %	3.10
hardness change, IRHD	3

These data are given as an indication of typical values and not as exact specifications.

## Industry and OEM specifications

<b>Sinopec DOT 3 Synthetic Brake Fluid meets the performance requirements of the following industry specifications:</b>	
FMVSS No. 116	DOT 3
GB <sup>1</sup>	12981-2012HZY3

<sup>1</sup> Note: 'GB' standards are the National Standards of the People's Republic of China.

## Accuracy of information

Data provided in this PDS is typical and subject to change as a result of continuing product research and development. The information given was correct at the time of printing. The typical values given are subject to variations in the testing procedures and the manufacturing process may also result in slight variations. Sinopec guarantees that its lubricants meet any industry and OEM specifications referred to on this data sheet.

Sinopec cannot be held responsible for any deterioration in the product due to incorrect storage or handling. Information on best practice is available from your local distributor.

## Product and environmental safety

This product should not cause any health problems when used in the applications suggested and when the guidance provided in the Material Safety Data Sheet (MSDS) is followed. Please consult the MSDS for more detailed advice on handling; MSDSs are available from your local distributor. Do not use the product in applications other than those suggested.

As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

The SINOPEC trademark is registered and protected.

Issued: March 2017

© Sinopec 2017

Sinopec DOT 3 Synthetic Brake Fluid